

Rittal – The System.

Faster – better – worldwide.

► TopTherm fan-and-filter units – SK 3241.100

Stand : Aug 26, 2013

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3241.100

created : 26.08.2013 on www.rittal.com/com-en



Produkt-Beschreibung

Colour: RAL 7035

Protection category to IEC 60 529: IP 54
With hose-proof hood: IP 56
With fine filter mat or hose-proof hood: IP 55

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat.

Packs of: 1 pc(s).

EAN: 4028177651982

Customs tariff number: 84145100

Produkt-Merkmale






Air throughput (unimpeded air flow): At 50 Hz: 230 m³/h
At 60 Hz: 250 m³/h

Air throughput with outlet filter including standard filter mat: Number of outlet filters: 1
2
1
Model No. of outlet filter :
SK 3240.200
SK 3240.200
SK 3243.200
At 50 Hz: 183 m³/h



203 m³/h
203 m³/h
At 60 Hz: 195 m³/h
230 m³/h
230 m³/h

Rated operating voltage:	230 V AC/1~/50 Hz 230 V AC/1~/60 Hz
Dimensions:	Width: 255 mm Height: 255 mm
Required mounting cut-out:	Width: 224 mm Height: 224 mm
Build depth:	25 mm
Installation depth:	107 mm
Temperature ranges:	Bearing: - 30 °C/+ 70 °C Operation (environment): - 30 °C - + 55 °C
Power consumption Pel:	At 50 Hz: 40 W At 60 Hz: 42 W
Rated current (max.):	At 50 Hz: 0.26 A At 60 Hz: 0.24 A
Pre-fuse:	Miniature circuit-breaker/fuse: 4 A
Noise level:	At 50 Hz: 54 dB(A) At 60 Hz: 56 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor




Approbationen

Certificates	Sorry, there is currently no information available
Declarations	 Declaration of conformity (EN, DE)
Approvals	 CSA (EN)  UR (EN)  C-UR (EN)  Approval overview (DE)

Downloads

Documentation	 Instructions (EN)  Instructions (DE)  Instructions (ES)  Instructions (FR)  Instructions (IT)  Instructions (JP)
----------------------	--

 Instructions (NL)
 Instructions (SV)

Characteristic curves	Sorry, there is currently no information available
Videos	Sorry, there is currently no information available
Data sheets	 Technical System Catalogue (DE)  Performance diagrams (DE)  Technical data sheet (DE)
CAD-Drawing	Request

Please note that there are the following alternative products:



TopTherm Filterlüfter EMV

Weitere Informationen zu diesem Produkt

» www.rittal.com/com-en/TopTherm_fan_and_filter_units



TopTherm Filterlüfter EMV

Rittal – The System.

Faster – better – worldwide.

- Enclosures
- Power distribution
- Climate control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postbox 1662 · D-35726 Herborn
Phone +49(0)2772 505-0 · Fax +49(0)2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

